
Harley-Davidson XL Sportster Coil and Ignition Key Relocation Kit 2007-2022

Mounting instructions



Coil relocation:

1. The coil should be removed from the stock brackets.
2. Remove 2 TORX screws from the top left side of the engine near the valve covers.
3. Before you mount the relocation bracket, install the coil on the bracket first.
4. In the back of your coil, there is an oval plate with 2 holes, put it in the inside of the bracket, line up the holes with the coil, and screw them in.
5. Put the coil and the bracket where the 2 TORX screws are (plug in the ignition coil before you fully tighten it).
6. Plug in your spark plug wires.

Key/Ignition relocation:

1. Remove the ground wire screwed in between the rear cylinder and the battery cover on the left side of the bike.
2. Install the ignition onto the bracket.
3. Install the bracket with the ignition on it into the ground location with the ground.

NOTE: Installation of this kit requires detailed knowledge of the motorcycle model and mechanics. It is assumed that the installer has access to the proper tools and a working knowledge of them and factory service manuals.

Harley-Davidson XL Sportster Coil and Ignition Key Relocation Kit 2007-2022

Mounting instructions



Coil relocation:

1. The coil should be removed from the stock brackets.
2. Remove 2 TORX screws from the top left side of the engine near the valve covers.
3. Before you mount the relocation bracket, install the coil on the bracket first.
4. In the back of your coil, there is an oval plate with 2 holes, put it in the inside of the bracket, line up the holes with the coil, and screw them in.
5. Put the coil and the bracket where the 2 TORX screws are (plug in the ignition coil before you fully tighten it).
6. Plug in your spark plug wires.

Key/Ignition relocation:

1. Remove the ground wire screwed in between the rear cylinder and the battery cover on the left side of the bike.
2. Install the ignition onto the bracket.
3. Install the bracket with the ignition on it into the ground location with the ground.

NOTE: Installation of this kit requires detailed knowledge of the motorcycle model and mechanics. It is assumed that the installer has access to the proper tools and a working knowledge of them and factory service manuals.