



# ASSEMBLY INSTRUCTIONS

## Short Bobber Softail Rear Fender and Seat Kit 2008-2017 "Short Oval"

RF-ST-200



For questions pertaining to the installation of this product, please contact our Killer Custom technical department at [info@killercustom.com](mailto:info@killercustom.com). This product is manufactured in Europe by Killer Custom

**NOTE:** Killer Custom assumes no responsibility or liability for damage or injury of any kind arising out of the use or misuse of any products.

1. Check all clearances before, during, and after installation.
2. Remove the OEM seat from the motorcycle.  
Note: The original seat cannot be used with the "Short Oval" rear fender. You must use the seat included in this kit.
3. Remove the OEM rear fender, including the side supports, ECM, and the license plate support bracket assembly.
4. Install the "Short Oval" rear fender onto the motorcycle. Adjust its position and secure it using the OEM bolts. The fender has pre-drilled mounting holes; however, in some cases minor adjustment of the hole shape or position may be required.
5. Reinstall the ECM. We recommend positioning the ECM between the seat and the fender. Ensure it is securely mounted in all cases.
6. Install the supplied seat onto the motorcycle. Installation is now complete.
7. Perform a test ride after installation to ensure all components are functioning correctly and securely.

### NOTE:

- Installation of this kit requires detailed knowledge of the specific motorcycle model and general motorcycle mechanics. It is assumed that the installer has access to proper tools and factory service manuals.
- Before painting, all parts must be test-fitted on the motorcycle to ensure correct alignment and proper fitment.
- This kit is designed for use with OEM shock absorbers. For improved aesthetics, a lowering kit or air ride suspension may be used.
- If you plan to ride the motorcycle on public roads, make sure to install the license plate and all required lighting equipment.

**[WWW.KILLERCUSTOM.COM](http://WWW.KILLERCUSTOM.COM)**